


Advantech AE Technical Share Document

Date	2020 / 06 / 17	Release Note	🗆 Internal 🔳 External
Category	■FAQ □SOP	Related OS	N/A
Abstract	How to connect the power cable of PCM-24U3 to TPC-xx51 series		
Keyword	PCM-24U2U3 / TPC-xx51T / TPC-1x51WP / idoor / power cable		
Related Product	TPC-xx51-E3AE/E3BE, TPC-1x51WP-E3AE, PCM-24U2U3		

Problem Description:

For PCM-24U2U3 it requires additional power to work. So it is important to connect the idoor power cable to the right connector of M/B. Since TPC-1x51 series have E3AE and E3BE version, the different version provide different connector for idoor power cable. PCM-24U2U3





Brief Solution:

Version A


TPC-1x51-E3AE (Resistive Touch Screen)

Since the connector on TPC-1x51-E3AE is 5 pin and the connector on idoor is 4 pin, it requires to order a 4pin to 5 pin cable to replace the original idoor power cable. P/N: 1700023725-01. Then connect the 1700023725-01 to CN 11 of M/B

1700023725-01










Version A

TPC-1x51WP-E3AE (Capacitive Touch Screen)

Since the CN11 connector of TPC-1x51WP-E3AE has been used, there is no connector for idol power. Please order an additional SATA cable and connect it to odor.

PN: 1700031368-01







There is no necessary to order an additional cable, just connect the original idoor power cable to CN24 connector.

