

PCI-1747U

250KS/s, 16-bit, 64-ch Analog Input Card with Universal PCI Bus

PIN Assignment

AI0	68	34	AI1
AI2	67	33	AI3
AI4	66	32	AI5
AI6	65	31	AI7
AI8	64	30	AI9
AI10	63	29	AI11
AI12	62	28	AI13
AI14	61	27	AI15
AGND	60	26	AGND
AI16	59	25	AI17
AI18	58	24	AI19
AI20	57	23	AI21
AI22	56	22	AI23
AI24	55	21	AI25
AI26	54	20	AI27
AI28	53	19	AI29
AI30	52	18	AI31
AI32	51	17	AI33
AI34	50	16	AI35
AI36	49	15	AI37
AI38	48	14	AI39
AI40	47	13	AI41
AI42	46	12	AI43
AI44	45	11	AI45
AI46	44	10	AI47
AGND	43	9	AGND
AI48	42	8	AI49
AI50	41	7	AI51
AI52	40	6	AI53
AI54	39	5	AI55
AI56	38	4	AI57
AI58	37	3	AI59
AI60	36	2	AI61
AI62	35	1	AI63

Signal Name	Reference	Direction	Description
AI<0..63>	AIGND	Input	Input Analog Input Channels 0 through 63. Each Channel pair, AI<i, i+1> (I = 0, 2, 4...62), can be configured as either two single-ended inputs or one differential input.
AIGND	-	-	Analog Input Ground. The ground reference is connected together on the PCI-1747U card.