

PCI-1762

16-ch Isolated Digital Input and 16-ch Relay Output Card

PIN Assignment

R11_OUT	62	42	21	R0_OUT	42	R6_OUT
R11_COM	61	41	20	R0_COM	41	R6_COM
R12_OUT	60	40	19	R1_OUT	40	R7_OUT
R12_COM	59	39	18	R1_COM	39	R7_COM
R13_OUT	58	38	17	R2_OUT	38	R8_OUT
R13_COM	57	37	16	R2_COM	37	R8_COM
R14_OUT	56	36	15	R3_OUT	36	R9_OUT
R14_COM	55	35	14	R3_COM	35	R9_COM
R15_OUT	54	34	13	R4_OUT	34	R10_OUT
R15_COM	53	33	12	R4_COM	33	R10_COM
NC	52	32	11	R5_OUT	32	NC
NC	51	31	10	R5_COM	31	NC
ECOM3	50	30	9	NC	30	NC
ECOM3	49	29	8	IDI15	29	IDI14
ECOM2	48	28	7	IDI13	28	IDI12
ECOM2	47	27	6	IDI11	27	IDI10
ECOM1	46	26	5	IDI9	26	IDI8
ECOM1	45	25	4	IDI7	25	IDI6
ECOM0	44	24	3	IDI5	24	IDI4
ECOM0	43	23	2	IDI3	23	IDI2
		22	1	IDI1	22	IDI0

Description of pin use:

IDI0 ~ IDI3:

Isolated digital input of group 0

IDI4 ~ IDI7:

Isolated digital input of group 1

IDI8 ~ IDI11:

Isolated digital input of group 2

IDI12 ~ IDI15:

Isolated digital input of group 3

ECOM0:

External common input of group 0

ECOM1:

External common input of group 1

ECOM2:

External common input of group 2

ECOM3:

External common input of group 3

NC:

No connection