

User Manual

PCI-7030

Intel[®] ATOM[™] N270 1.6GHz FSB533MHz, PCI Half-size SBC with Dual GbE LAN/LVDS/DVI/ 2 SATA/6 COM (2 COMs on board, plus 4 COMs by module)

Trusted ePlatform Services



Copyright

The documentation and the software included with this product are copyrighted 2009 by Advantech Co., Ltd. All rights are reserved. Advantech Co., Ltd. reserves the right to make improvements in the products described in this manual at any time without notice. No part of this manual may be reproduced, copied, translated or transmitted in any form or by any means without the prior written permission of Advantech Co., Ltd. Information provided in this manual is intended to be accurate and reliable. However, Advantech Co., Ltd. assumes no responsibility for its use, nor for any infringements of the rights of third parties, which may result from its use.

Acknowledgements

AWARD is a trademark of Phoenix Technologies Ltd.

IBM and PC are trademarks of International Business Machines Corporation.

Intel[®] Atom[™] N270 is trademark of Intel Corporation

WinBond is a trademark of Winbond Corporation.

All other product names or trademarks are properties of their respective owners.

Part No. 2002703000 Printed in Taiwan Edition 1 April 2009

A Message to the Customer

Advantech Customer Services

Each and every Advantech product is built to the most exacting specifications to ensure reliable performance in the harsh and demanding conditions typical of industrial environments. Whether your new Advantech equipment is destined for the laboratory or the factory floor, you can be assured that your product will provide the reliability and ease of operation for which the name Advantech has come to be known.

Your satisfaction is our primary concern. Here is a guide to Advantech's customer services. To ensure you get the full benefit of our services, please follow the instructions below carefully.

Technical Support and Assistance

- 1. Visit the Advantech web site at www.advantech.com/support where you can find the latest information about the product.
- 2. Contact your distributor, sales representative, or Advantech's customer service center for technical support if you need additional assistance. Please have the following information ready before you call:
 - Product name and serial number
 - Description of your peripheral attachments
 - Description of your software (operating system, version, application software,
 - etc.)
 - A complete description of the problem
 - The exact wording of any error messages

Declaration of Conformity

FCC

This device complies with the requirements in part 15 of the FCC rules:

Operation is subject to the following two conditions:

- This device may not cause harmful interference
- This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this device in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his/her own expense. The user is advised that any equipment changes or modifications not expressly approved by the party responsible for compliance would void the compliance to FCC regulations and therefore, the user's authority to operate the equipment.





Caution! There is a danger of a new battery exploding if it is incorrectly installed. Do not attempt to recharge, force open, or heat the battery. Replace the battery only with the same or equivalent type recommended by the manufacturer. Discard used batteries according to the manufacturer's instructions.

Memory Compatibility

Brand	Size	Speed	Vendor PN	Advantech PN	Memory
Transcend	512MB	DDR2 533	119833-0266	NA	Infineon HYB18T512 800AF37 SVV39006 0526 (32x8)
	2GB	DDR2 533	TS256MSQ6 4V5U	NA	Micron D9HNL (128x8)
	256MB	DDR2 533	78.82054.42 0	NA	ELPIDA JAPAN E5116AB- 5C-E 05050WPWA (64x8)
Apacer	512MB	DDR2 533	78.92051.42 1	96D2- 512M533NN-AP1	ELPIDA JAPAN E5108AB- 5C-E 04520WR5Q (64x8)
	1GB	DDR2 533	78.02051.42 3	96D2-1G533NN- AP1	ELPIDA TWN E5108AE- 5C-E (64x8)
	256MB	DDR2 667	TS32MSQ64 V6M	NA	Hynix HY5PS121621B FP- Y5 (32x16)
Transcend (RoHS)	512MB	DDR2 667	TS6QSJ2300 2-6S/ TS64MSQ64 V6J	96SD2- 512M667NN-TR	SAMSUNG K4T51083QC ZCE6 (64x8)
	1GB	DDR2 667	TS128MSQ6 4V6J	NA	SAMSUNG K4T51083QC ZCE6 (64x8)
	2GB	DDR2 667	TS5QSU273 00-6M	96SD2- 2G667NN-TR	Micron D9HNL (128x8)
Apacer	512MB	DDR2 667	78.92G63.42 2	NA	ELPIDA E5108AG-6E-E (64x8)
(RoHS)	1GB	DDR2 667	78.02G63.42 3	96SD2- 1G667NN-AP	ELPIDA E5108AGBG-6E-E (64x8)
	256MB	DDR2 667	NA	NA	ELPIDA E5116AF-6E-E (32x16)
DSL	512MB	DDR2 667	NA	NA	ELPIDA E5108AGBG-6E-E (64x8)
(RoHS)	1GB	DDR2 667	NA	NA	ELPIDA E5108AGBG-6E-E (64x8)
	2GB	DDR2 667	NA	NA	ELPIDA E1108ACSE-6E-E (128x8)
Transcend	1GB	DDR2 800	TS128MSQ6 4V8J	NA	HYNIX HY5PS12821E-FP- S5 (64x8)
(RoHS)	2GB	DDR2 800	TS256MSQ6 4V8U	NA	Micron D9HNP (128x8)
DSL	1GB	DDR2 800	NA	NA	ELPIDA TWN E5108AHSE-8E-E (64x8)
(RoHS)	2GB	DDR2 800	NA	NA	ELPIDA JPN E1108ACSE- 8E-E (128x8)

Ordering Information

P/N	On-board processor	Chipset	VGA	LVDS	DVI	USB	LAN
PCI-7030VG-00A1E	ATOM N270 1.6G	945GSE	Yes	Yes	-	6	1 (82574L)
PCI-7030G2-00A1E	ATOM N270 1.6G	945GSE	Yes	Yes	Yes	5	2 (82574L)

Product Warranty (2 years)

Advantech warrants to you, the original purchaser, that each of its products will be free from defects in materials and workmanship for two years from the date of purchase.

This warranty does not apply to any products which have been repaired or altered by persons other than repair personnel authorized by Advantech, or which have been subject to misuse, abuse, accident or improper installation. Advantech assumes no liability under the terms of this warranty as a consequence of such events.

Because of Advantech's high quality-control standards and rigorous testing, most of our customers never need to use our repair service. If an Advantech product is defective, it will be repaired or replaced at no charge during the warranty period. For outof-warranty repairs, you will be billed according to the cost of replacement materials, service time and freight. Please consult your dealer for more details.

If you think you have a defective product, follow these steps:

- 1. Collect all the information about the problem encountered. (For example, CPU speed, Advantech products used, other hardware and software used, etc.) Note anything abnormal and list any onscreen messages you get when the problem occurs.
- 2. Call your dealer and describe the problem. Please have your manual, product, and any helpful information readily available.
- 3. If your product is diagnosed as defective, obtain an RMA (return merchandise authorization) number from your dealer. This allows us to process your return more quickly.
- 4. Carefully pack the defective product, a fully-completed Repair and Replacement Order Card and a photocopy proof of purchase date (such as your sales receipt) in a shippable container. A product returned without proof of the purchase date is not eligible for warranty service.
- 5. Write the RMA number visibly on the outside of the package and ship it prepaid to your dealer.

Packing List

Before setting up the system, check that the items listed below are included and in good condition. If any item does not accord with the table, please contact your dealer immediately.

Part Number	Description	Quantity
1700060202	Y-cable for PS/2 Keyboard, PS/2 Mouse	x 1
1701340603	FDD cable (600 mm)	x 1
170000265	Power cable	x 1
1700002343	ATX feature cable	x 1
1703150102	Serial ATA HDD power cable	x 1
1700003194	Serial ATA HDD data cable	x 1
1701400452	EIDE (HDD) cable	x 1
1700002223	Parallel port Cable (2.0 mm w/BKT)	x 1
1700008887	USB cable with 4 ports (2.0 mm pitch)	x 1
1700008762	Dual-COM port cable kit for COM1-2	x 1
9689000002	Jumper pack	

If any of these items are missing or damaged, contact your distributor or sales representative immediately. We have carefully inspected the PCI-7030 mechanically and electrically before shipment. It should be free of marks and scratches and in perfect working order upon receipt. As you unpack the PCI-7030, check it for signs of shipping damage. (For example, damaged box, scratches, dents, etc.) If it is damaged or it fails to meet the specifications, notify our service department or your local sales representative immediately. Also notify the carrier. Retain the shipping carton and packing material for inspection by the carrier. After inspection, we will make arrangements to repair or replace the unit.

Contents

Chapter	1	General Information	1
	1.1	Introduction	2
	1.2	Features	2
	1.3	Specifications	3
		1.3.1 System	3
		1.3.2 Memory	3
		1.3.3 Input/Output	3
		1.3.4 Graphics	3
		1.3.5 Ethernet LAN	3
		1.3.6 Industrial features	3
		1.3.7 Mechanical and environmental specifications	4
	1.4	Jumpers and Connectors	4
		Table 1.1: Jumpers	4
		Table 1.2: Connectors	5
	1.5	Board layout: Jumper and Connector Locations	6
		Figure 1.1 Jumper and Connector Location	6
	4.0	Figure 1.2 I/O Connectors	6
	1.6	PCI-7030 Board Diagram	/
	4 7	Figure 1.3 PCI-7030 Board Diagram	/
	1.7	Safety Precautions	ð
	1.8	Jumper Settings	9
			9
		T.0.2 CMOS Clear (CMOST)	10
		1 9 2 II //D1: L CD Dowor 2 2 //5 // Solootor	10
		Table 1.4: II V/1/II V/2: LCD Power 3.3 V/5 V Selector	10
		1.8.4 IWDT1: Watchdog Timer Output Ontion	11
		Table 1.5: IWDT1: Watchdog Timer Output Option	11
	10	System Memory	1 1 11
	1.9	Memory Installation Procedures	11 11

Chapter 2 Connecting Peripherals13

2.1	Introduction	
2.2	Front Panel Connectors (JFP1 & JFP2)	14
2.3	IR Connector (JIR1)	
2.4	IDE Connector (IDE1)	15
2.5	Compact Flash card Socket (CF1)	15
2.6	Floppy Connector (FDD1)	15
2.7	Parallel Port (LPT1)	
2.8	USB Ports (USB12/USB34)	
2.9	Serial ATA Interface (SATA1, SATA2)	17
2.10	Serial Ports (COM12)	17
2.11	PS/2 Keyboard / Mouse connector (KBMS1 & 2)	
2.12	VGA Connector (VGA1)	
2.13	LAN RJ45 connector (LAN12)	
2.14	LAN LED connector (LANLED1/LANLED2)	19
	Table 2.1: Front Panel LAN indicator connector	
2.15	ATX Feature connector(ATXF1)	20
2.16	ATX power control connector (ATX1)	21
2.17	CPU FAN connector (CPUFAN1)	21
2.18	System FAN connector (SYSFAN1)	
2.19	Audio Interface Connector (HDAUD1)	
2.20	GPIO Header (GPIO1)	23

	2.21	DVI LCD panel connector(DVI1)	
	2.22	Low Pin Count Header (LPC1)	
	2.23	SM Bus Connector (SMBLIS1)	
	2.23	LVDS Connector (LVDS1)	24
	2.25	LCD Inverter Connector (INV1)	
	•		07
Chapter	3	BIOS Operation	27
	3.1	Introduction	
	3.2	BIOS Setup	
		3.2.1 Main Menu	
		3.2.2 Standard CMOS Features	
		3.2.3 Advanced BIOS Features	
		3.2.4 Advanced Unipset Features	
		2.2.6 USP Dovice Setting	
		3.2.7 Security Chip Configuration (Ontional Itom)	
		3.2.8 TPM Support	
		3.2.0 Power Management Setun	
		3.2.10 PnP/PCI Configurations	39 11
		3.2.10 PC Health Status	۱+ 12
		3.2.17 Frequency///oltage Control	<u>۲</u> ۲ 43
		3.2.13 Load Setup Defaults	
		3 2 14 Set Password	
		3.2.15 Save & Exit Setup	46
		3.2.16 Quit without Saving	
Chapter	4 4.1 4.2 4.3	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup.	48 48 48 49
Chapter Chapter	4 4.1 4.2 4.3 5	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup	48 48 49 49
Chapter Chapter	4 4.1 4.2 4.3 5	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup VGA Setup	48 48 49 49 52
Chapter Chapter	4 4.1 4.2 4.3 5 5.1 5.2	Chipset Software Installation Utility Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000	48 48 49 51
Chapter Chapter	4 4.1 4.2 4.3 5 5.1 5.2	Chipset Software Installation Utility Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000	48 48 49 51 52 52 52
Chapter Chapter Chapter	4.1 4.2 4.3 5 5.1 5.2 6	Chipset Software Installation Utility Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration	48 48 49 51 52 52 52 53
Chapter Chapter Chapter	4 4.1 4.2 4.3 5 5.1 5.2 6 6.1	Chipset Software Installation Utility Before You Begin Introduction Windows XP Driver Setup. VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Introduction	48 48 49 51 52 52 53
Chapter Chapter Chapter	4 4.1 4.2 4.3 5 5.1 5.2 6 6.1 6.2	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Introduction Introduction Introduction Windows Vista/XP/2000	48 48 49 51 52 52 53
Chapter Chapter Chapter	 4.1 4.2 4.3 5 5.1 5.2 6 6.1 6.2 6.3 	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Introduction Installation Win XP/Vista Driver Setup	48 48 49 51 52 52 53 54 54 54
Chapter Chapter Chapter	4 4.1 4.2 4.3 5 5 5.1 5.2 6 6 6.1 6.2 6.3 × A	Chipset Software Installation Utility Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Introduction Installation Win XP/Vista Driver Setup Programming the Watchdog Time	ty 47 48 49 51 51 52 52 53 53 54 54 54 54 54 54
Chapter Chapter Chapter	4 4.1 4.2 4.3 5 5 5.1 5.2 6 6 6.1 6.2 6.3 × A A.1	Chipset Software Installation Utility Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Installation Win XP/Vista Driver Setup Programming the Watchdog Timer	ty 47 48 49 51 51 52 52 53 53 54 54 54 54 7. 55
Chapter Chapter Chapter Appendi	4 4.1 4.2 4.3 5 5.1 5.2 6 6 6.1 6.2 6.3 × A A.1	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Installation Win XP/Vista Driver Setup Programming the Watchdog Timer A.1.1 Watchdog Timer	ty 47 48 49 51 51 52 52 53 54 54 54 r. 55 56 56
Chapter Chapter Chapter Appendi	4 4.1 4.2 4.3 5 5.1 5.2 6 6.1 6.2 6.3 × A A.1	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Installation Win XP/Vista Driver Setup Programming the Watchdog Timer A.1.1 Watchdog Timer Overview A.1.2	ty 47 48 48 49 51 52 52 53 54 54 r. 55 56 56 56 56 56
Chapter Chapter Chapter Appendi	4 4.1 4.2 4.3 5 5.1 5.2 6 6.1 6.2 6.3 × A A.1	Chipset Software Installation Utilit Before You Begin Introduction Windows XP Driver Setup VGA Setup Introduction Windows Vista/XP/2000 LAN Configuration Introduction Installation Win XP/Vista Driver Setup Programming the Watchdog Timer A.1.1 Watchdog Timer A.1.2 Programming the Watchdog Timer A.1.2 Programming the Watchdog Timer A.1.2 Programming the Watchdog Timer A.1.2 Watchdog Timer A.1.2 Programming the Watchdog Timer A.1.2 Watchdog Timer A.1.2	ty 47 48 48 49 51 51 52 52 53 53 r. 55 r. 55 56 56 56 56 56 58

Appendix B I/O Pin Assignments......61

B.1	Front Panel Connectors (JFP1) Table B 1: Front Panel Connectors (JFP1)	62 62
B.2	Front Panel Connectors (JFP2)	62
B.3	USB Ports (USB12/USB34)	62 62
	Table B.3: USB Ports (USB12/USB34)	62
B.4	IR Connector (JIR1)	63
D 5	Table B.4: IR Connector (JIR1)	63
D.3	Table B 5 [°] Serial Ports (COM12)	03
B.6	PS/2 Keyboard / Mouse connector (KBMS2)	64
	Table B.6: PS/2 Keyboard / Mouse connector (KBMS2)	64
B.7	LAN LED connector (LANLED1/LANLED2)	64
	Table B.7: LAN LED connector (LANLED1/LANLED2)	64
B.8	AIX Feature connector(AIXF1)	64
PO	CPUEAN connector (CPUEAN1)	64
D.9	Table B 9 [°] CPU FAN connector (CPUFAN1)	05
B.10	System FAN connector (SYSFAN1)	65
	Table B.10:System FAN connector (SYSFAN1)	65
B.11	Audio Interface Connector (HDAUD1)	65
	Table B.11:Audio Interface Connector (HDAUD1)	65
B.12	GPIO Header (GPIO1)	66
D 40	Table B.12:GPIO Header (GPIO1)	66
B.13	Table B 13:DVI LCD panel connector (DVI1)	00
R 14	I VDS Connector (I VDS1)	00
0.11	Table B.14:LVDS Connector (LVDS1)	67
B.15	LCD Inverter Connector (INV1)	67
	Table B.15:LCD Inverter Connector (INV1)	67
B.16	SM Bus Connector (SMBUS1)	68
	Table B.16:SM Bus Connector (SMBUS1)	68
B.17	Low Pin Count Header (LPC1)	68
D 10	ATX nower centrel connector (ATX1)	80
0.10	Table B 18:ATX power control connector (ATX1)	09 60
B.19	VGA Connector (VGA1)	69
-	Table B.19:VGA Connector (VGA1)	69

Appendix CSystem Assignments71

C.1	System I/O Ports	
	Table C.1: System I/O Ports	72
C.2	DMA Channel Assignments	
	Table C.2: DMA Channel Assignments	73
C.3	Interrupt Assignments	73
	Table C.3: Interrupt Assignments	73
C.4	1st MB Memory Map	73
	Table C.4: 1st MB Memory Map	73
C.2 C.3 C.4	 DMA Channel Assignments	7 7 7 7 7 7 7 7 7 7



General Information

1.1 Introduction

The PCI-7030 series is a half-sized CPU card designed with the Intel[®] 945GSE and the ICH7M for industrial applications that require both performance computing and enhanced power management capabilities. The PCI-7030 series has on board CPU Intel[®] Atom[™] N270 1.6GHz with 533 MHz front side bus and DDR2 533 MHz up to 2 GB.

The PCI-7030 offers cost-saving integrated graphics, built on the Intel[®] 945GSE chipset and features the unique Intel[®] Extreme Graphics architecture that maximizes VGA performance and shares system memory up to 224 MB.

Advantech PCI-7030 is designed as Ultra Low power and Fanless with an Intel[®] 945GSE chipset and on board CPU Intel ATOM N270 1.6GHz FSB 533 MHz processor. A rich I/O connectivity of 6 serial ports by extra module, 6 USB 2.0, Dual Intel GbE LAN and 2 SATA ports at most.

1.2 Features

- Multiple expansion feature: PIC-7030 is PCI Half-sized slot CPU card with easy for upgrade and maintenance.
- Cost effective 945GSE chipset: support 533 Front side bus
- Rich I/O connectivity: 6 serial ports by LPC module, 6 USB 2.0, Dual Intel GbE LAN
- Wide selection of storage devices: IDE HDD, SATA HDD, CF, customers benefit from the flexibility of using the most suitable storage device for larger capacity
- Optimized integrated graphic solution: With Intel[®] Graphics Media Accelerator 950, supports versatile display options and 32-bit 3D graphics engine. Support VGA, 18/36 bits LVDS, DVI display.

1.3 Specifications

1.3.1 System

- CPU: Intel[®] Atom[™] N270 1.6 GHz FSB 533 MHz
- BIOS: Award SPI 8 Mbit BIOS
- System chipset: Intel[®] 945GSE with ICH7M
- SATA hard disk drive interface: Two on-board SATA connectors with data transmission rate up to 150 MB
- IDE Interface: One onboard IDE connector supporting up to two enhanced IDE devices. Supports PIO mode 4 (16.67 MB/s data transfer rate) and ATA 33/66/ 100 (33/66/100 MB/s data transfer rate) BIOS enabled/disabled
- **CF interface:** Supports compact flash Type II

1.3.2 Memory

RAM: Up to 2 GB in 1 slots 200-pin SODIMM sockets. Supports single channel DDRII 533 SDRAM

1.3.3 Input/Output

- **PCI bus:** Support 32/33MHz PCI 4 Slots to backplane.
- Enhanced parallel port: Configured to LPT1, with 25 pin box header. Supports EPP/SPP/ECP
- Serial ports: Six serial ports, 2 x RS-232 onboard, 4 x RS-422/485 w/Auto-flow by PCA-COM485 module or 4 x RS-232 by PCA-COM232 module.
- Keyboard and PS/2 mouse connector: Two 6-pin mini-DIN connectors are located on the mounting bracket for easy connection to a PS/2 keyboard and mouse
- USB port: Supports up to 6 USB2.0 for PCI-7030VG (2 on real IO); 5 USB2.0 for PCI-7030G2 (1 on real IO) with 480 Mbps; 4 ports onboard.
- **GPIO connector:** 16-bit general purpose Input/Output

1.3.4 Graphics

- **Controller:** Chipset integrated VGA controller
- Display memory: Dynamically shared system memory up to 224 MB
- **CRT:** Up to 2048 x 1536 resolution, 400 MHz RAMDAC
- LVDS: Supports single channel 18-bit/ dual channel 36-bit LVDS, Up to UXGA 1600 x 1200
- DVI: Support Maximum pixel lock of 400 MHz, up to 2048 x 1536 resolutions @ 75 Hz refresh rate

1.3.5 Ethernet LAN

- Supporting dual 10/100/1000 Mbps Ethernet port (s) via PCI Express x1 bus which provides 500 MB/s data transmission rate
- **Controller:** Intel 82574L Chipset

1.3.6 Industrial features

Watchdog timer: Can generate a system reset. The watchdog timer is programmable and can be set from 1 to 255 seconds or 1 to 255 minutes.

1.3.7 Mechanical and environmental specifications

- Operating temperature: 0 ~ 60° C (32 ~ 140° F) (operating humidity: 40°C @ 85% RH Non-Condensing)
- **Storage temperature:** -20 ~ 70° C (-4 ~ 158° F)
- **Humidity:** 5 ~ 95% non-condensing
- Power supply voltage: +5 V, +12 V, 5 Vsb
- Power consumption:

+12 V @ 0.31 A, +5 V @ 2.19 A, +3.3 V @ 0 A,+5 VSB @ 0.04 A, +2 V @ 0 A Measuring the maximum current value with system under maximum load (ATOM 1.6G + DDR2 533 / 2G)

- Board size: 185 mm (L) x 122 mm (W) (7.3" x 4.8")
- Board weight: 0.365 kg

1.4 Jumpers and Connectors

Connectors on the PCI-7030 CPU card link it to external devices such as hard disk drives and a keyboard. In addition, the board has a number of jumpers used to configure your system for your application.

The tables below list the function of each of the board jumpers and connectors. Later sections in this chapter give instructions on setting jumpers. Chapter 2 gives instructions for connecting external devices to your CPU card.

Table 1.1: Jumpers	
Label	Function
CMOS1	CMOS clear
JLVDS1	LVDS voltage selection
JWDT1	Watchdog timer output selection

Table 1.2: Connect	ors		
Label	Function		
JFP1(1-2)	HDD LED connector		
JFP1(3-4)	Power LED connector		
JFP1(5-6)	Suspend LED connector		
JFP1(7-8)	Reset connector		
JFP1(9-10)	ATX soft power switch		
JFP2(1-2)	FAN fail LED Connector		
JFP2(3-4)	Thermal fail LED Connector		
DIMMA1	DDR2 SODIMM Socket		
JIR1	IR connector		
IDE1	IDE connector		
CF1	CF Socket		
FDD1	FDD connector		
LPT1	Parallel port		
USB12	USB port 1,2		
USB34	USB port 3,4		
USB5	USB port 5		
SATA1	Serial ATA1		
SATA2	Serial ATA2		
COM12	Serial Port: COM1 COM2		
KBMS1	PS/2 keyboard and mouse connector		
KBMS2	External keyboard and mouse connector		
VGA1	VGA connector		
LAN12	Dual Gigabit Ethernet connector (LAN1 LAN2)		
LANLED1	Front Panel LAN Indicator connector for LAN1		
LANLED2	Front Panel LAN Indicator connector for LAN2		
ATXF1	ATX feature connector		
ATX1	ATX power connector		
CPUFAN1	CPU FAN connector (3-pin)		
SYSFAN1	System FAN connector (3-pin)		
HDAUD1	High Definition audio connector		
GPIO1	GPIO pin header		
BT1	RTC battery connector		
DVI1	DVI connector		
LPC1	LPC connector		
SPI_CN1	SPI flash programming connector		
U16	SPI flash socket		
SMBUS1	SM BUS connector		
LVDS1	LVDS connector		
INV1	Inverter connector		

1.5 Board layout: Jumper and Connector Locations



Figure 1.1 Jumper and Connector Location



Figure 1.2 I/O Connectors

1.6 PCI-7030 Board Diagram





Safety Precautions 1.7



Warning! Always completely disconnect the power cord from chassis whenever you work with the hardware. Do not make connections while the power is on. Sensitive electronic components can be damaged by sudden power surges. Only experienced electronics personnel should open the PC chassis.



Caution! Always ground yourself to remove any static charge before touching the motherboard. Modern electronic devices are very sensitive to electrostatic discharges. As a safety precaution, use a grounding wrist strap at all times. Place all electronic components on a static-dissipative surface or in a static-shielded bag when they are not in the chassis.





Caution! The computer is provided with a battery-powered real-time clock circuit. There is a danger of explosion if battery is incorrectly replaced. Replace only with same or equivalent type recommended by the manufacturer. Discard used batteries according to manufacturer's instructions.



Caution! There is a danger of a new battery exploding if it is incorrectly installed. Do not attempt to recharge, force open, or heat the battery. Replace the battery only with the same or equivalent type recommended by the manufacturer. Discard used batteries according to the manufacturer's instructions.

1.8 Jumper Settings

This section provides instructions on how to configure your motherboard by setting the jumpers. It also includes the motherboards's default settings and your options for each jumper.

1.8.1 How to Set Jumpers

You can configure your motherboard to match the needs of your application by setting the jumpers. A jumper is a metal bridge that closes an electrical circuit. It consists of two metal pins and a small metal clip (often protected by a plastic cover) that slides over the pins to connect them. To "close" (or turn ON) a jumper, you connect the pins with the clip. To "open" (or turn OFF) a jumper, you remove the clip. Sometimes a jumper consists of a set of three pins, labeled 1, 2, and 3. In this case you connect either pins 1 and 2, or 2 and 3.



The jumper settings are schematically depicted in this manual as follows:



A pair of needle-nose pliers may be helpful when working with jumpers.

If you have any doubts about the best hardware configuration for your application, contact your local distributor or sales representative before you make any changes. Generally, you simply need a standard cable to make most connections.

1.8.2 CMOS Clear (CMOS1)

To avoid damaging the computer, always turn off the power supply before setting "Clear CMOS". Before turning on the power supply, set the jumper back to "3.0 V Battery On". This jumper is used to erase CMOS data and reset system BIOS Information.

The procedure for clearing CMOS is:

- 1. Turn off the system.
- 2. Short pin 2 and pin 3.
- 3. Turn on the system. The BIOS is now reset to its default setting.

Table 1.3: CMOS	1	
Function	Jumper Setting	
*Keep CMOS data	1	1-2 closed
Clear CMOS data		2-3 closed
* Default		

* Default

1.8.3 JLVD1: LCD Power 3.3 V/5 V Selector

Table 1.4: JLV1/JLV2: LCD Power 3.3 V/5 V Selector			
Closed Pins	Result		
1-2*	3.3 V*		
2-3	5 V		

*Default

1	_1
0 0 0	000
3.3 V 1-2 closed	5 V 2-3 closed

1.8.4 JWDT1: Watchdog Timer Output Option

Table 1.5: JWDT1: Watchdog Timer Output Option		
Closed Pins	Result	
1-2	NC	
2-3*	System Reset*	

*Default



The following sections tell how to make each connection. In most cases, you will simply need to connect a standard cable. All of the connector pin assignments are shown in Appendix B.



Warning! Always completely disconnect the power cord from your chassis whenever you are working on it. Do not make connections while the power is on. Sensitive electronic components can be damaged by a sudden rush of power. Only experienced electronics personnel should open the PC chassis.



Caution! Always ground yourself to remove any static charge before touching the CPU card. Modern electronic devices are very sensitive to static electric charges. Use a grounding wrist strap at all times. Place all electronic components on a static-dissipative surface or in a static-shielded bag when they are not in the chassis.

1.9 **System Memory**

The PCI-7030 series has one socket for a 200-pin SODIMMx1.

This sockets use 1.8 V un-buffered double data rate synchronous DRAMs (DDR SDRAM). They are available in capacities of 256, 512, and 1024 MB. The sockets can be filled in any combination with DIMMs of any size, giving a total memory size between 256 MB and 2 GB. PCI-7030 series does NOT support ECC (error checking and correction).

1.10 Memory Installation Procedures

To install SODIMMs, first make sure the two handles of the SODIMM socket are in the "open" position. i.e. The handles lean outward. Slowly slide the SODIMM module along the plastic guides on both ends of the socket. Then press the SODIMM module right down into the socket, until you hear a click. This is when the two handles have automatically locked the memory module into the correct position of the SODIMM socket. To remove the memory module, just push both handles outward, and the memory module will be ejected by the mechanism in the socket.



Connecting Peripherals

2.1 Introduction

You can access most of the connectors from the top of the board as it is being installed in the chassis. If you have a number of cards installed or have a packed chassis, you may need to partially remove the card to make all the connections.

2.2 Front Panel Connectors (JFP1 & JFP2)



There are several external switches to monitor and control the PCI-7030.

2.3 IR Connector (JIR1)



This connector supports the optional wireless infrared transmitting and receiving module. This module mounts on the system case. You must configure the setting through BIOS setup.

2.4 IDE Connector (IDE1)



The PCI-7030 provides an IDE channel to which you can attach up to two Enhanced Integrated Device Electronics hard disk drives or CDROM to the board's internal controller.

One onboard IDE connector supporting up to two enhanced IDE devices (CF card is regarded as one IDE device). Supports PIO mode 4 (16.67 MB/s data transfer rate) and ATA 33/66/100 (33/66/100 MB/s data transfer rate) BIOS enabled/disabled

2.5 Compact Flash card Socket (CF1)

The board provides a CompactFlash card type I/II socket. The CompactFlash card shares the IDE channel.





You can attach one floppy drive to the PCI-7030. You can use any combination of 5.25" (360 KB and 1.2 MB) and/ or 3.5" (720 KB, 1.44 MB, and 2.88 MB) drives.

2.7 Parallel Port (LPT1)



The parallel port is normally used to connect the motherboard to a printer. The PCI-7030 includes an onboard parallel port, accessed through a 25-pin flat-cable connector, LPT1.

2.8 USB Ports (USB12/USB34)



PCI-7030VG-00A1E provides up to six USBs: USB12, USB34, plus two from real I/O. (PCI-7030G2-00A1E provides up to five: USB12, USB34, plus one from real I/O.) This gives complete Plug & Play and hot swapping for over a hundred external devices. The USB interface complies with USB Specification Rev. 2.0, supporting transmission rate up to 480 Mbps and is fuse protected. The USB interface can be disabled in the system BIOS setup.

2.9 Serial ATA Interface (SATA1, SATA2)



PCI-7030 features a high performance Serial ATA interface (up to 150 MB/s) which eases cabling to hard drives with long, thin cables.

2.10 Serial Ports (COM12)



The PCI-7030 offers two serial ports: COM1 & COM2. These ports can connect to serial devices, such as a mouse or to a communications network. The IRQ and address ranges for all ports are fixed. However, if you want to disable the port or change these parameters later, you can do this in the system BIOS setup.

Different devices implement the RS-232 standard in different ways. If you are having problems with a serial device, be sure to check the pin assignments for the connector.

2.11 PS/2 Keyboard / Mouse connector (KBMS1 & 2)



One 6-pin mini-DIN connectors (KBMS1) on the card mounting bracket provide connection to a PS/2 keyboard and a PS/2 mouse, respectively. KBMS2 (5-pin 2.54mm wafer box) can also be connected to an adapter cable (P/N: 1700060202, available from Advantech) for connecting to both a PS/2 keyboard.

2.12 VGA Connector (VGA1)



The PCI-7030 includes a VGA interface that can drive conventional CRT displays. VGA1 is a standard 15-pin D-SUB connector commonly used for VGA. Pin assignments for CRT connector VGA1 are detailed in Appendix B.

2.13 LAN RJ45 connector (LAN12)



PCI-7030 uses the Intel 82574L Gigabit LAN chip which is linked to PCIe x1 Link. With this chip, PCI-7030 may provide high throughputs for a heavy load networking environment. It provides one or two RJ-45 connectors in the rear side and is convenient for most industrial applications. PCI-7030G2 provides two Gigabit LAN and PCI-7030VG provides one Gigabit LAN.

2.14 LAN LED connector (LANLED1/LANLED2)



PCI-7030 provides an external LAN LED Pin header for connecting to the front side of the chassis. With this convenient design users can easily see whether the LAN port is active or not. Refer to Appendix B for detailed information on the pin assignments



Table 2.1: Front Panel LAN indicator connector				
LAN Mode	LED1	LED2		
1000Mbps Link On	Green On	On		
1000Mbps Active	Green on	Green Flashes		
1000Mbps Link Off	Off	Off		
100Mbps Link On	Orange On	Green On		
100Mbps Active	Orange On	Green Flashes		
100Mbps Link Off	Off	Off		
10Mbps Link On	Off	Green On		
10Mbps Active Off	Green	Flashes		
10Mbps Link Off	Off	Off		

2.15 ATX Feature connector(ATXF1)



The PCI-7030 can support an advanced soft power switch function, if an ATX power supply is used. To enable the soft power switch function:

- 1. Get the specially designed ATX-to-EBX power cable
- 2. Connect the 3-pin plug of the cable to ATXF1 (ATX feature connector).
- 3. Connect the power on/off button to JPF1(9-10)

Default value is set ATXF1 to short pin1-2.

Important Make sure that the ATX power supply can take at least a 10mA load on the 5V standby lead (5 VSB). If not, you may have difficulty powering on your system.

2.16 ATX power control connector (ATX1)



The PCI-7030 support ATX power. ATX1 supplies main power (+5V,+12V, 5VSB), and it is a 6 x 2 power connector

2.17 CPU FAN connector (CPUFAN1)



The PCI-7030 is equipped with a 3-pin FAN connector providing +12 V power for CPU FAN.

2.18 System FAN connector (SYSFAN1)



The PCI-7030 is equipped with a 3-pin FAN connector providing +12 V power for system FAN.

2.19 Audio Interface Connector (HDAUD1)



The Audio Interface link is a 10 pin connector, the PCI-7030 can support Audio with the addition of optional PCE-AUDIO-HDA1E. For detailed pin assignments, refer to Appendix B.

2.20 GPIO Header (GPIO1)



Provides a 10-pin header for Digital I/O usage. Refer to Appendix B for detailed information on the pin assignments.

The board supports 8-bit GPIO through GPIO connector. The 8 digital in- and outputs can be programmed to read or control devices, with input or out- put defined. This GPIO is CMOS level ($0 \sim 5V$).

2.21 DVI LCD panel connector(DVI1)



Digital Visual Interface (DVI) is the standard interface for high-performance connection between PCs and Flat Panel Displays, Digital CRT displays, Projectors, and HDTV. The PCI-7030 is able to drive a DVI connector display at a pixel resolution up to maximum pixel lock of 400 MHz up to 2048 x 1536 resolutions @ 75 Hz

2.21.0.1 Panel type and Resolution mode selection

Customer can select display type and boot number from BIOS menu selection.

2.22 Low Pin Count Header (LPC1)

PCI-7030 provides a 14-pin header for LPC module. Refer to Appendix B for detailed information on the pin assignments. Here are the LPC modules that you can choose.

Table 2.2: LPC Module		
Part Number	Description	
PCA-COM485	4 x 422/485 COM module with auto-flow control	
PCA-COM232	4 x 232 COM module	

2.23 SM Bus Connector (SMBUS1)



4-pin connector reserved for extra SMBus device.

2.24 LVDS Connector (LVDS1)


For PCI-7030, LVDS1 consists of a 40-pin connector which can support 18/36-bit up to UXGA 1600 x 1200

2.25 LCD Inverter Connector (INV1)



The LCD inverter is connected to INV1 via a 5-pin connector to provide power to the LCD display.



BIOS Operation

3.1 Introduction

Advantech provides a full-featured Award BIOS that delivers superior performance, compatibility and functionality for manufactures of Industrial PCs and embedded boards; its many options and extensions let you customize your products to a wide range of designs and target markets.

The modular, adaptable AwardBIOS supports the broadest range of third-party peripherals and all popular chipsets, plus $Intel^{(R)}$, AMD, nVidia, VIA, and compatible CPUs from 386 through Pentium^(R) and AMD GeodeTM, K7 and K8 (including multiple processor platforms), and VIA Eden C3 and C7 CPUs.

You can use Advantech's utilities to select and install features to suit your design needs.

3.2 BIOS Setup

The PCI-7030 Series system has built-in AwardBIOS with a CMOS SETUP utility which allows users to configure required settings or to activate certain system features.

The CMOS SETUP saves the configuration in the CMOS RAM of the motherboard. When the power is turned off, the battery on the board supplies the necessary power to the CMOS RAM.

When the power is turned on, pressing the button during the BIOS POST (Power-On Self Test) will take you to the CMOS SETUP screen.

Control Keys	
$< \uparrow >< \downarrow >< \leftarrow >< \rightarrow >$	Move to select item
<enter></enter>	Select Item
<esc></esc>	Main Menu - Quit and not save changes into CMOS Sub Menu - Exit current page and return to Main Menu
<page +="" up=""></page>	Increase the numeric value or make changes
<page -="" down=""></page>	Decrease the numeric value or make changes
<f1></f1>	General help, for Setup Sub Menu
<f2></f2>	Item Help
<f5></f5>	Load Previous Values
<f7></f7>	Load Setup Default
<f10></f10>	Save all CMOS changes

3.2.1 Main Menu

Press to enter AwardBIOS CMOS Setup Utility, the Main Menu will appear on the screen. Use arrow keys to select among the items and press <Enter> to accept or enter the sub-menu.

Phoenix - AwardBIOS	CMOS Setup Utility
 Standard CMOS Features Advanced BIOS Features Advanced Chipset Features Integrated Peripherals Security Chip Configuration Power Management Setup PnP/PCI Configurations 	 PC Health Status Frequency/Voltage Control Load SetUp Defaults Set Password Save & Exit Setup Exit Hithout Saving
Esc : Quit F10 : Save & Exit Setup	↑↓→← : Select Item
Time, Date, Hard Disk Type	

Standard CMOS Features

This setup page includes all the items in standard compatible BIOS.

Advanced BIOS Features This setup page includes all the items of Award BIOS enhanced features.

Advanced Chipset Features

This setup page includes all the items of Chipset configuration features.

Integrated Peripherals

This setup page includes all onboard peripheral devices.

Security chip configuration

This SETUP page includes all the items of Trusted Module Configuration features. This sub-menu item only appears when the Trusted Module is plugged in.

Power Management Setup This setup page includes all the items of Power Management features.

PnP/PCI Configurations

This setup page includes PnP OS and PCI device configuration.

PC Health Status

This setup page includes the system auto detect CPU and system temperature, voltage, fan speed.

Frequency/Voltage Control

This setup page includes CPU host clock control, frequency ratio and voltage.

Load Setup Defaults

This setup page includes Load system optimized value, and the system would be in best performance configuration.

Set Password

Establish, change or disable password.

Save & Exit Setup

Save CMOS value settings to CMOS and exit BIOS setup.

Exit Without Saving

Abandon all CMOS value changes and exit BIOS setup.

3.2.2 Standard CMOS Features

Phoen	ix - AwardBIOS CMOS Setup Standard CMOS Features	Jtility
Date (mm:dd:yy) Time (hh:mm:ss) IDE Channel Ø Master IDE Channel Ø Slave IDE Channel 1 Master IDE Channel 1 Slave Drive A Drive B Video Halt On	Sun, Apr 5 2009 14 : 12 : 51 [None] [None] [None] [None] [1.44M, 3.5 in.] [None] [EGA/VGA] [All Errors]	Item Help Menu Level ► Change the day, month, year and century
Base Memory Extended Memory Total Memory	639K 1038336K 1039360K	
↑↓→←:Move Enter:Select F5:Previous V	+/-/PU/PD:Value F10:Save alues F7: Set	ESC:Exit F1:General Help Jp Defaults

Date

The date format is <weekday>, <month>, <day>, <year>.

Weekday	From Sun to Sat, determined and displayed by BIOS only
Month	From Jan. to Dec.
Day	From 1 to 31
Year	From 1999 through 2098

Time

The time format is <hour> <minute> <second>, based on 24-hour time.

IDE Channel 0 Master/Slave

IDE HDD Auto-Detection Press "Enter" for automatic device detection.

Video

Select EGA or VGA display.

Halt on

The item determines whether the computer will stop if an error is detected during power up.

No Errors	The system boot will not stop for any error.
All Errors	Whenever the BIOS detects a non-fatal error the system will be stopped.
All, But Keyboard	The system boot will not stop for a keyboard error; it will stop for all other errors. (Default value)

Base Memory

The POST of the BIOS will determine the amount of base (or conventional) memory installed in the system.

Extended Memory

The BIOS POST will determine the amount of extended memory (above 1 MB in CPU's memory address map) installed in the system.

Total Memory

This item displays the total system memory size.

3.2.3 Advanced BIOS Features



CPU Feature

This item allows users to adjust CPU features.

Hard Disk Boot Priority

This item allows users to select boot sequence for system device HDD, USB-HDD, SCSI, RAID.

Virus Warning [Disabled]

Enables or disables the virus warning.

CPU L1 & L2 Cache [Enabled]

This item allows users to enable CPU L1 and L2 cache.

CPU L3 Cache

This item allows users to enable CPU L3 cache.

Hyper-Threading Technology

While using a CPU with Hyper-Threading technology, you can select "Enabled" to enable Hyper-Threading Technology in an OS which supports Hyper-Threading Technology or select "Disabled" for other OSs which do not support Hyper-Threading technology.

Quick Power On Self Test [Enabled]

This field speeds up the Power-On Self Test (POST) routine by skipping retesting a second, third and forth time. Setup setting default is enabled.

First / Second / Third / Other Boot Drive

Hard Disk	Select boot device priority by Hard Disk.
CDROM	Select boot device priority by CDROM.
USB-FDD	Select boot device priority by USB-FDD.

USB-ZIP	Select boot device priority by USB-ZIP.
USB-CDROM	Select boot device priority by USB-CDROM.
LAN	Select boot device priority by LAN.
Disabled	Disable this boot function.

Gate A20 Option [Fast]

This item enables users to switch A20 control by port 92 or not.

Typematic Rate Setting

This item enables users to set the two typematic controls items.

- Typematic Rate (Chars/Sec)

This item controls the speed at which the system registers auto-repeated keystrokes. The eight settings are 6, 8, 10, 12, 15, 20, 24 and 30.

- Typematic Delay (Msec)

This item sets the keypress time delay before autorepeat begins.

Four delay rate options are 250, 500, 750 and 1000.

value).

Security Option [Setup]

SystemSystem will not boot and refuses access to Setup page if the cor-
rect password is not entered at the prompt.SetupSystem will boot, but access to Setup requires password (default

APIC Mode [Enabled]

This item allows user to enabled of disabled "Advanced Programmable Interrupt Controller". APIC is implemented in the motherboard and must be supported by the operating system, and it extends the number of IRQ's available.

3.2.4 Advanced Chipset Features



Note!

This "Advanced Chipset Features" page controls configuration of the board's chipset. This page is chipset dependent; screens may differ somewhat depending on the chipset. It is strongly recommended that only technical users make changes to the default settings.

DRAM Timing Selectable [By SPD]

This item enables users to set the optimal timings for items 2 through 5; system default setting "By SPD" follows the SPD information and ensures the system runs stably with optimal performance.

CAS Latency Time [Auto]

This item enables users to set the timing delay in clock cycles before SDRAM starts a read command after receiving it.

DRAM RAS# to CAS# Delay [Auto]

This item enables users to set the timing of the transition from RAS (row address strobe) to CAS (column address strobe) as both rows and column are separately addressed shortly after DRAM is refreshed.

DRAM RAS# Precharge [Auto]

This item enables users to set the DRAM RAS# precharge timing, system default is setting to "Auto" to reference the data from SPD ROM.

Precharge delay (tRAS) [Auto]

This item allows user to adjust memory precharge time.

Video BIOS Cacheable [Disabled]

This item allows the video BIOS to be cached to allow faster execution and better performance.

On-Chip Frame Buffer Size [8 MB]

This item allows the user to adjust the on-chip frame buffer size 8 MB or 1 MB.

DVMT Mode [DVMT]

This item allows the user to adjust Intel's Dynamic Video Memory Technology (DVMT). BIOS provides three options: DVMT, FIXED, and Both.

DVMT/FIXED Memory Size [128MB]

This item allows the user to adjust DVMT/FIXED graphics memory size.

Boot Display

This item allows the user to decide boot display mode.

Panel Number

This item allows the user to decide display resolution.

Init Display First

This item is the setting for start up video output: either from PCI Express or Onboard device.

3.2.5 Integrated Peripherals

Phoen	ix - AwardBIOS CMOS Setup Integrated Peripherals	Utility
► OnChip IDE Device	[Press Enter]	Item Help
 ► SuperIO Device ► USB Device Setting 	[Press Enter] [Press Enter] [Press Enter]	Menu Level ►
↑↓→←:Move Enter:Select F5:Previous U	+/-/PU/PD:Value F10:Save	e ESC:Exit F1:General Help

Note!

This "Integrated Peripherals" page controls the configuration of the board's chipset, including IDE, ATA, SATA, USB, AC97, MC97 and Super IO and Sensor devices. This page is chipset dependent; the screen capture above is illustrative, but screens do differ depending on chipset features.

OnChip IDE Device

This item enables users to set the OnChip IDE device status, including some of new chipsets also support SATA devices (Serial-ATA).

Phoenix -	AwardBIOS CMOS Setup Ut: OnChip IDE Device	ility
IDE HDD Block Mode	[Enabled]	Item Help
On-Chip Primary PCI IDE	[Enabled]	Menu Level 🕨
IDE Primary Slave PIO	[Auto]	If your IDE hard drive
IDE Frimary Slave UDMA	[Auto] [Fnabled]	supports prock mode select Enabled for
IDE Secondary Master PIO	[Auto]	the optimal number of
IDE Secondary Master UDMA	[Auto]	sector the drive can
were On-Chin Sovial OTO So	tting www	Support
On-Chin Serial ATA		
× SATA PORT Speed Settings	Disabled	
× PATA IDE Mode	Secondary	
SATA Port	P0,P2 is Primary	
r ^↓→+:Move Enter:Select +/- F5:Previous Value	/PU/PD:Value F10:Save J s F7: SetUp	SC:Exit F1:General Help Defaults

Onboard Device

This item enables users to set the Onboard device status, including enabling AC97, and LAN devices.

Phoenix - AwardBIOS Cl	IOS Setup Utility
Onboard De	evice
Azalia/AC97 Audio Select [Auto] Dubgard LAN1 control [Fnabled]	Item Help
Onboard LAN1 ROM [Disabled] Onboard LAN2 control [Enabled] Onboard LAN2 ROM [Disabled]	Menu Level ►
↑↓→←:Move Enter:Select +/-/PU/PD:Value	F10:Save ESC:Exit F1:General Help
F5:Previous Values	F7: SetUp Defaults

Super IO Device

This item enables users to set the Super IO device status, including enabling of COM, and LPT.

Phoenix	- AwardBIOS CM SuperIO Devi	OS Setup Uti ce	ility	
KBC input clock	[8 MHz]	<u> </u>	Ite	m Help
Onboard FDC Controller	[Enabled]		Contraction of the second	
Unboard Serial Port 1 Onboard Sorial Port 2	[3]8/[KU4] [2F8/[D03]		Menu Level	
HART Mode Select	[Normall			
× UR2 Duplex Mode	Half			
Onboard Parallel Port	[378/IRQ7]			
Parallel Port Mode	LECP+EPP1			
ECP Mode Use DMA	[3]			
CIR Port Address	[Disabled]			
x CIR Port IRU	11			
Unboard Serial Port 3 Onboard Serial Port 4				
Onboard Serial Port 5				
Anhoard Serial Port 6				
Onboard Serial Port 7	[C80/IRQ11]			
COM7 Auto Direction	[Disabled]			
Onboard Serial Port 8	[C88/IRQ11]			
COM8 Auto Direction	[Disabled]			
↑↓→+:Move Enter:Select +/	-/PU/PD:Value	F10:Save I	SC:Exit F1	:General Help
F5:Previous Valu	es	F7: SetUp	Defaults	

CKB input clock [8 MHz]

PS/2 keyboard communicates with the keyboard controller. The speed of the data link depends on the clock signal generated by the keyboard controller.

Onboard FDC Controller [Enable]

When enabled, this field allows you to connect your floppy disk drives to the onboard floppy disk drive connector instead of a separate controller card. If you want to use a different controller card to connect the floppy disk drives, set this field to Disabled.

	Onboard Serial port 1 [3F8 / IRQ4]
	This item allows user to adjust serial port 1 of address and IRQ.
	Onboard Serial port 2 [2F8/ IRQ3]
	This item allows user to adjust serial port 2 of address and IRQ.
	UART Mode select [Normal]
	This item allows you to select UART mode.
	Onboard Parallel Port [378/IRQ7]
	This item allows user to adjust parallel port of address and IRQ.
	Parallel Port Mode [ECP+EPP]
	This item allows user to adjust parallel port mode.
	ECP Mode Use DMA [3]
	This item allows user to adjust ECP DMA resource.
	CIR Port Address [Disable]
	This item allows user to adjust CIR port of address and IRQ.
	Onboard Serial port 3 [CA0/IRQ10]
	This item allows user to adjust serial port 3 of address and IRQ.
	Onboard Serial port 4 [CA8/IRQ10]
	This item allows user to adjust serial port 4 of address and IRQ.
	Onboard Serial port 5 [CB8/IRQ10]
	This item allows user to adjust serial port 5 of address and IRQ.
	Onboard Serial port 6 [CB8/IRQ10]
_	This item allows user to adjust serial port 6 of address and IRQ.
	Onboard Serial port 7 [C80/IRQ11]
	I his item allows user to adjust serial port 7 of address and IRQ.
_	I his serial port 7 need to be provided by LPC module (optional)
	COM/ Auto Direction [Disable]
	norted
	Onboard Serial port 8 [C88/IRO11]
_	This item allows user to adjust serial port 8 of address and IRO
	This serial port 8 need to be provided by LPC module (optional)
	COM8 Auto Direction [Disable]
_	This item allows user to enable Auto-Flow control function of COM8 if sup-
	ported.
	Onboard Serial port 9 [C90/IRQ11]
	This item allows user to adjust serial port 9 of address and IRQ.
	This serial port 9 need to be provided by LPC module (optional)
	COM9 Auto Direction [Disable]
	This item allows user to enable Auto-Flow control function of COM9 if sup-
	ported.
	Onboard Serial port 10 [C98/IRQ11]
	This item allows user to adjust serial port 10 of address and IRQ.
	This serial port 10 need to be provided by LPC module (optional)
	COM10 Auto Direction [Disable]
	This item allows user to enable Auto-Flow control function of COM10 if sup-
	poneu.

3.2.6 USB Device Setting

Phoenix	 AwardBIOS CMOS Setup USB Device Setting 	Utility
USB 1.0 Controller USB 2.0 Controller USB Operation Mode USB Keyboard Function USB Mouse Function USB Storage Function *** USB Mass Storage Dev	[Enabled] [Enabled] [High Speed] [Enabled] [Enabled] [Enabled] pice Boot Setting ***	Item HelpMenu Level ►[Enable] or [Disable]Universal HostController Interfacefor Universal Serial
		Bus.
^↓→+:Move Enter:Select +/ F5:Previous Valu	/-/PU/PD:Value F10:Save les F7: Set	e ESC:Exit F1:General Help Up Defaults

USB 1.0 Controller

Select.Enabled. if your system contains a Universal Serial Bus (USB) controller and you have USB peripherals. The choices are "Enabled" and "Disabled".

USB 2.0 Controller

This entry is used to disable/enable the USB 2.0 controller only. The BIOS itself may or may not have high-speed USB support. If the BIOS has high speed USB support built in, the support will automatically turn on when a high speed device is attached. The choices are "Enabled" or "Disabled".

USB Operation Mode

Set the USB 2.0 controller to Hi Speed (480 Mbps) or Full Speed (12 Mbps).

USB Keyboard / Mouse Function

Select "Enabled" if you plan to use a USB keyboard/Mouse. The choices are "Enabled" and "Disabled".

USB Storage Function

Select "Enabled" if you plan to use an external USB storage device to boot system under DOS mode. The choices are "Enabled" and "Disabled".

3.2.7 Security Chip Configuration (Optional Item)

	Phoenix Sec	- AwardBIOS CM urity Chip Com	IOS Setup Ut figuration	ility		
TPM Suppor TPM Curren	rt nt Status	[Disabled] Enabled & D	leactivated	Item Help		
× TPM Status	S.	No change		Menu Level 🔸		
				Enable/Disable Trusted Platform Module.		
A L V A MOULO	-t		F10+9-10-	FSC:Fuit F1:Comerce Hole		
T↓→←:Move Li F:	5:Previous Valu	es	F10:Save F7: SetUp	Defaults		

3.2.8 TPM Support

The items in this menu allow you to set the TPM (Trusted Platform Module) features. Select an item and then press <Enabled> to display the configuration options.

Note!

To enable the TPM function, set the TPM Support item to [Enabled] and then save the change; after rebooting, the TPM configuration menu will show the active options.

3.2.9 Power Management Setup

Power-Supply Type	[ATX]	4	Item Help
Pup HGARIOS if S3 Posume			Menu Teuel 🕨
Power Management	[User Define]		Henn Devel
Video Off Method	ENPMS 1		
Video Off In Suspend	[Yes]		
Suspend Type	[Stop Grant]		
Suspend Mode	[Disabled]		
Soft-Off by PWR-BTTN	[Instant-Off]		
CPU THRM-Throttling	[50.0%]		
PowerOn by LAN	[Disabled]		
PowerOn by Modem	[Disabled]		
PowerOn by Alarm	[Disabled]		
x Date(of Month) Alarm	0		
x Time(hh:mm:ss) Alarm	0:0:0		
** Reload Global Timer Ev	ents **		
Primary IDE 0	[Disabled]		
Primary IDE 1	[Disabled]		

Note!

Adjust "Power management Setup" to configure the system to most effective energy savings still consistent with the intended style of use.

Power-Supply Type [ATX]

This item allows user to set power-supply type, ATX or AT mode.

ACPI Suspend Type [S3(STR)]

This item allows user to select sleep state when in suspend.

S1(POS)	The suspend mode is equivalent to a software power down;
S3(STR)	The system shuts down with the exception of a refresh current to
	the system memory.

Run VGA BIOS if S3 Resume [Auto]

This item allows system to reinitialize VGA BIOS after system resume from ACPI S3 mode.

Power Management [User Define]

This item allows user to select system power saving mode.

Min Saving	Minimum power management. Suspend Mode=1 hr.
Max Saving	Maximum power management. Suspend Mode=1 min.
User Define	Allows user to set each mode individually. Suspend Mode= Disabled or 1 min \sim 1 hr.

Video Off Method [DPMS]

This item allows user to determine the manner is which the monitor is blanked.

V/H SYNC+Blank	This option will cause system to turn off vertical and horizontal syn-
	chronization ports and write blanks to the video buffer.
Blank Screen	This option only writes blanks to the video buffer.

DPMS Initial display power management signaling.

Video Off In Suspend [Yes]

This item allows users to turn off video when system is in suspend mode.

Suspend Type [Stop Grant]

This item allows users to determine the suspend type.

Suspend Mode [Disabled]

This item allows users to set a delay time. If system inactivity exceeds the delay time, all devices except the CPU will be shut off.

Soft-Off by PWR-BTTN [Instant-Off]

This item allows users to define function of power button.

Instant-Off Press power button for instant power off.

Delay 4 Sec Press power button for four seconds to initiate power off.

CPU THRM-Throttling

The ability is control how much percent of your CPU's clock speed will be throttled down when the CPU overheat. You can set "75.0%", "50.0%", and "25.0%".

PowerOn by LAN [Enabled]

This item allows users to power on the system via LAN. The choices are "Enabled" and "Disabled".

PowerOn by Modem [Enabled]

This item allows users to power on the system by Modem. The choices are "Enabled" and "Disabled".

PowerOn by Alarm [Disabled]

The choices are "Enabled" and "Disabled". If enabled, the fields that follow indicate dates and times of alarm settings.

Primary IDE 0 (1) and Secondary IDE 0 (1)

When Enabled, the system will resume from suspend mode if Primary IDE 0 (1) or Secondary IDE 0 (1) becomes active. The choices are "Enabled" and "Disabled".

FDD, COM, LPT PORT

When Enabled, the system will resume from suspend mode if the FDD, interface, COM port, or LPT port is active. The choices are "Enabled" and "Disabled".

PCI PIRQ [A-D]#

When Enabled, the system resumes from suspend mode if an interrupt occurs. The choices are "Enabled" and "Disabled".

PWRON After PWR-Fail [ON/Off/Former-Sts]

Use this to set up the system after power failure. The "Off" setting keeps the system powered off after power failure, the "On" setting boots up the system after failure, and the "Former-Sts" returns the system to the status before power failure.

3.2.10 PnP/PCI Configurations

Reset Co	onfiguration Data	[Disabled]	Item Help
Resource × IRQ Reso × DMA Reso	es Controlled By purces purces	LAuto(ESCD)] Press Enter Press Enter	Menu Level Default is Disabled. Select Enabled to reset Extended System Configuration Data ESCD) when you exit Setup if you have installed a new add-on and the system reconfiguration has caused such a serious conflict that the OS cannot boot

Reset Configuration Data [Disabled]

The default is Disabled. Select Enabled to reset Extended System Configuration Data (ESCD) if you have installed a new add-on card, and system configuration is in such a state that the OS cannot boot.

Resources Controlled By [Auto(ESCD)]

The commands here are "Auto(ESCD)" or "Manual". Choosing "Manual" requires you to choose resources from the following sub-menu. "Auto(ESCD)" automatically configures all of the boot and Plug and Play devices, but you must be using Windows 95 or above.

3.2.11 PC Health Status

hutdown Temperature	[Disabled]	Item Help
PU Warning Temperature Case Open Warning Poore -3.30 -50 -120 SUSB PBat CPU Temperature YSTEM Temperature 'an 1 Speed 'an 2 Speed	LDISADIEAJ (Disabled) 0.88V 3.32V 4.94V 11.96V 4.94V 2.88V 33°C 36°C 0 RPM 0 RPM	Menu Level ►

Shutdown Temperature [Disabled]

The system will shut down automatically if the CPU temperature goes over the selected setting.

CPU Warning Temperature [Disabled]

The system will give an automatic warning if the CPU temperature goes over the selected setting.

Case Open Warning [Disabled] Enable this to detect if the case is open or closed.

VCORE and Other Voltages

This shows the voltage of VCORE, +3.3 V, +5 V, +12 V, 5VSB, VBat(V)

CPU Temperature

This shows the current CPU temperature.

SYSTEM Temperature

This shows the current temperature of the system.

FAN 1 Speed

This shows the current FAN 1 operating speed.

FAN 2 Speed

This shows the current FAN 2 operating speed.

3.2.12 Frequency/Voltage Control

	Phoenix - AwardBIOS CMOS Setup Utility Frequency/Voltage Control						
Auto De	tect PCI Clk	[Enabled]			Item	Help	
CPU Hos	t/SRC/PCI Clock	[Default]		Menu Le	vel	*	
↑↓→←∶Move	Enter:Select F5:Previous Va	+/-/PU/PD:Value lues	F10:Save F7: SetUr	ESC:Exit Defaults	F1:6	enera l	Help

Auto Detect PCI Clk [Enabled]

This item enables users to set the PCI Clock by system automatic detection or by manual.

Spread Spectrum [Disabled] This item enables users to set the spread spectrum modulation.

CPU Host/SRC/PCI Clock [Default]

This item enables users to set the CPU Host and PCI clock by system automatic detection or by manual.

3.2.13 Load Setup Defaults



Note!

Load Setup Defaults loads the default system values directly from ROM. Useful if the stored record created by the Setup program should ever become corrupted (and therefore unusable).

3.2.14 Set Password



Note!

To enable this feature, you should first go to the Advanced BIOS Features menu, choose the Security Option, and select either Setup or System, depending on which aspect you want password protected. "Setup" requires a password only to enter Setup. "System" requires the password either to enter Setup or to boot the system. A password can be at most 8 characters long. To Establish Password

- 1. Choose the Set Password option from the CMOS Setup Utility main menu and press <Enter>.
- When you see "Enter Password", enter the desired password and press <Enter>.
- 3. At the "Confirm Password" prompt, retype the desired password, then press <Enter>.
- 4. Select Save to CMOS and EXIT, type <Y>, then <Enter>.

To Change Password

- 1. Choose the Set Password option from the CMOS Setup Utility main menu and press <Enter>.
- 2. When you see "Enter Password", enter the existing password and press <Enter>.
- 3. You will see "Confirm Password". Type it again, and press < Enter>.
- 4. Select Set Password again, and at the "Enter Password" prompt, enter the new password and press <Enter>.
- 5. At the "Confirm Password" prompt, retype the new password, and press <Enter>.
- 6. Select Save to CMOS and EXIT, type <Y>, then <Enter>.

To Disable Password

- 1. Choose the Set Password option from the CMOS Setup Utility main menu and press <Enter>.
- 2. When you see "Enter Password", enter the existing password and press <Enter>.
- 3. You will see "Confirm Password". Type it again, and press < Enter>.
- 4. Select Set Password again, and at the "Enter Password" prompt, please don't enter anything; just press <Enter>.
- 5. At the "Confirm Password" prompt, again, don't type in anything; just press <Enter>.
- 6. Select Save to CMOS and EXIT, type <Y>, then <Enter>.

3.2.15 Save & Exit Setup

Phoenix - AwardBIOS	CMOS Setup Utility		
 Standard CMOS Features Advanced BIOS Features Advanced Chipset Features Integrated Peripherals 	 PC Health Status Frequency/Voltage Control Load SetUp Defaults Set Password 		
 Power Management PnP/PCI Configura 	SAVE to CMOS and EXIT (Y/N)? Saving		
Esc : Quit F10 : Save & Exit Setup			
Save Data to CMOS			

Note! Typing "Y" will quit the BIOS Setup Utility and save user setup values to CMOS.

Typing "N" will return to BIOS Setup Utility.

3.2.16 Quit without Saving



Note!



Typing "Y" will quit the BIOS Setup Utility without saving to CMOS. Typing "N" will return to BIOS Setup Utility.



Chipset Software Installation Utility

4.1 Before You Begin

To facilitate the installation of the enhanced display drivers and utility software, read the instructions in this chapter carefully. The drivers for the AIMB-210 are located on the software installation CD. The driver in the folder of the driver CD will guide and link you to the utilities and drivers under a Windows system. Updates are provided via Service Packs from Microsoft*.



The files on the software installation CD are compressed. Do not attempt to install the drivers by copying the files manually. You must use the supplied SETUP program to install the drivers.

Before you begin, it is important to note that most display drivers need to have the relevant software application already installed in the system prior to installing the enhanced display drivers. In addition, many of the installation procedures assume that you are familiar with both the relevant software applications and operating system commands. Review the relevant operating system commands and the pertinent sections of your application software's user manual before performing the installation.

4.2 Introduction

The Intel[®] Chipset Software Installation (CSI) utility installs the Windows INF files that outline to the operating system how the chipset components will be configured. This is needed for the proper functioning of the following features:

- Core PCI PnP services
- IDE Ultra ATA 100/66/33 and Serial ATA interface support
- USB 1.1/2.0 support (USB 2.0 driver needs to be installed separately for Win98)
- Identification of Intel[®] chipset components in the Device Manager
- Integrates superior video features. These include filtered sealing of 720 pixel DVD content, and MPEG-2 motion compensation for software DVD

Note!

This utility is used for the following versions of Windows, and it has to be installed **before** installing all the other drivers:



- Windows 2000
- Windows XP
- Windows Vista

4.3 Windows XP Driver Setup

1. Insert the driver CD into your system's CD-ROM drive. You can see the driver folder items. Navigate to the "Drv_INF" folder and click "infinst_autol.exe" to complete the installation of the driver.







VGA Setup

5.1 Introduction

To benefit from the Intel[®] 945GSE integrated graphics controller, you need to install the VGA driver. The Intel[®] 945GSE integrated graphics controller includes the following features:

Intel[®] Graphics Media Accelerator 950: Incorporating the latest Microsoft[®] DirectX 9 support capabilities. Dual independent display, enhanced display modes for widescreen flat panels, and optimized 3D support deliver an intense and realistic visual experience without requiring a separate graphics card.

5.2 Windows Vista/XP/2000



Before installing this driver, make sure the CSI utility has been installed in your system. See Chapter 4 for information on installing the CSI utility.

Insert the driver CD into your system's CD-ROM drive. You can see the driver folders items. Navigate to the "Drv_VGA" folder and click "setup.exe" to complete the installation of the drivers for Vista, Windows XP, and Windows 2000.





LAN Configuration

6.1 Introduction

The PCI-7030 has a dual Gigabit Ethernet LAN via dedicated PCI Express x 1 bus (Intel82574L), which offers bandwidth of up to 500 MB/sec, eliminating the bottleneck of network data flow and incorporating Gigabit Ethernet to operate at 1000Mbps.Features

6.2 Installation



Before installing the LAN drivers, make sure the CSI utility has been installed on your system. See Chapter 4 for information on installing the CSI utility.

The PCI-7030 Intel82574L Gigabit integrated controller supports all major network operating systems. However, the installation procedure varies with different operating systems. Please find and use the section that provides the driver setup procedure for the operating system you are using.

6.3 Win XP/Vista Driver Setup

Insert the driver CD into your system's CD-ROM drive. Select the Drv_LAN folder then navigate to the directory for your OS.





Programming the Watchdog Timer

A.1 Programming the Watchdog Timer

The PCI-7030's watchdog timer can be used to monitor system software operation and take corrective action if the software fails to function within the programmed period. This section describes the operation of the watchdog timer and how to program it.

A.1.1 Watchdog Timer Overview

The watchdog timer is built into the super I/O controller IT8718F. It provides the following user-programmable functions:

- Can be enabled and disabled by user program
- Timer can be set from 1 to 65535 seconds or 1 to 65535 minutes
- Generates an interrupt or resets signal if the software fails to reset the timer before time-out

A.1.2 Programming the Watchdog Timer

The I/O port address of the watchdog timer is 2E (hex) and 2F (hex). 2E (hex) is the address port. 2F (hex) is the data port. You must first assign the address of register by writing an address value into address port 2E (hex), then write/read data to/from the assigned register through data port 2F (hex).



Table A.1: Watchdog	Timer Regis	ters	
Address of Register (2E)	Attribute		
Read/Write	Value (2F) & description		
87(hex)/01(hex)/55(hex)/			
9 (hex)/01(hex)/55(hex)/ 55(Write this value to I/O address port 2E (hex)	
55(hex)		to unlock the IT8718F.	
07 (hex)	write	Write 07 (hex) to select LDN (Logic Device Number)	
		of GPIO Configuration Register	
72 (hex)	write	Set seconds or minutes as units for the timer.	
		Write 0 to bit 7: set minute as counting unit.	
		[default]	
		Write 1 to bit 7: set second as counting unit.	
73 (hex)	Read/write	Watch Dog Timer-out Value (LSB)	
74 (hex)	Read/write	Watch Dog Timer-out Value (MSB)	
		74&73 value 01~FFFF (hex): The amount of the count, in seconds	
		or minutes, depends on the value set in register 72	
		(hex). This number decides how long the watch-	
		dog timer waits for strobe before generating an	
		interrupt or reset signal. Writing a new value to this	
		register can reset the timer to count with the new	
AA (hex)		value.	
		IT8718F.	

Appendix A Programming the Watchdog Time

A.1.3 Example Program

;-----

1. Enable watchdog timer and set 10 sec. as timeout interval

mov dx,2eh ; Unlock IT8718F mov al,87h out dx,al mov al.01h out dx,al mov al,55h out dx,al mov al,55h out dx,al ;----mov dx,2eh ; Select LDN of GPIO ConfigurationRegister mov al,07h out dx,al inc dx mov al.07h out dx.al ;---- Set second as counting unit -----mov dx,2eh mov al,72h out dx,al inc dx in al,dx or al,80h out dx,al :----mov dx,2eh ; Set timeout interval as 10 seconds and start counting mov al,74h out dx,al inc dx mov al,00h out dx,al mov dx,2eh mov al,73h out dx,al inc dx mov al, 0Ah out dx, al :----mov dx,2eh ; Lock IT8718F mov al,0aah out dx,al ;


I/O Pin Assignments

B.1 Front Panel Connectors (JFP1)

2	4	6	8	10
0	0	0	0	0
0	0	0	0	0
1	3	5	7	9

Table B.1: Front Panel Connectors (JFP1)			
Pin	Signal	Pin	Signal
1	HDD LED+	2	HDD LED-
3	Power LED+	4	Power LED-
5	Suspend LED+	6	Suspend LED-
7	System Reset Button	8	GND
9	ATX Power Button	10	GND

B.2 Front Panel Connectors (JFP2)

1	2	3	4
	0	0	0

Table B.2: Panel Connectors (JFP2)	
Pin	Signal
1	FAN Fail LED +
2	FAN Fail LED -
3	Thermal Fail LED +
4	Thermal Fail LED -

B.3 USB Ports (USB12/USB34)



Table B.3: USB Ports (USB12/USB34)				
Pin	Signal	Pin	Signal	
1	VCC	2	VCC	
3	USB Data1-	4	USB Data2-	
5	USB Data1+	6	USB Data2+	
7	GND	8	GND	
9	GND	10		

B.4 IR Connector (JIR1)

	1
0	2
0	3
0	4
0	5

Table B.4: IR Connector (JIR1)		
Pin	Signal	
1	VCC	
2	NC	
3	IR_RX	
4	GND	
5	IR_TX	

B.5 Serial Ports (COM12)

2 4	18 20
0000000	0000
	0000
1 3	17 19

Table B	Table B.5: Serial Ports (COM12)			
Pin	Signal	Pin	Signal	
1	DCD1	2	DSR1	
3	RX1	4	RTS1	
5	TX1	6	CTS1	
7	DTR1	8	RI1	
9	GND	10	GND	
11	DCD2	12	DSR2	
13	RX2	14	RTS2	
15	TX2	16	CTS2	
17	DTR2	18	RI2	
19	GND	20	GND	

B.6 PS/2 Keyboard / Mouse connector (KBMS2)



Table B.6: PS/2 Keyboard / Mouse connector (KBMS2)		
Pin	Signal	
1	PS2 keyboard clock	
2	PS2 keyboard data	
3	PS2 mouse data	
4	GND	
5	VCC	
6	PS2 mouse clock	

B.7 LAN LED connector (LANLED1/LANLED2)

Table B.7: LAN LED connector (LANLED1/LANLED2)			
Pin	Signal	Pin	Signal
1	LAN1_LINK/ACTIVITY#	2	LAN1_1000#
3	VCC3	4	LAN1_100#

B.8 ATX Feature connector(ATXF1)



Table B.8: ATX Feature connector(ATXF1)	
Pin	Signal
1	5V standby
2	VCC
3	PS_ON#

B.9 CPU FAN connector (CPUFAN1)



Table B.9: CPU FAN connector (CPUFAN1)			
Pin	Signal		
1	FAN_PWM		
2	+12V		
3	FAN_TACH		

B.10 System FAN connector (SYSFAN1)



Table B.10: System FAN connector (SYSFAN1)			
Pin	Signal		
1	FAN_PWM		
2	+12V		
3	FAN_TACH		

B.11 Audio Interface Connector (HDAUD1)

2	4	6	8	10	
0	0	0	0	0	
0	0	0	0	0	0
1	3	5	7	9	11

Table B.	Table B.11: Audio Interface Connector (HDAUD1)				
Pin	Signal	Pin	Signal		
1	ACZ_VCC	2	GND		
3	ACZ_SYNC	4	ACZ_BITCLK		
5	ACZ_SDOUT	6	ACZ_SDIN0		
7	ACZ_SDIN1	8	ACZ_RST#		
9	ACZ_12V	10	GND		
11	GND	12			

B.12 GPIO Header (GPIO1)

9	7	5	3	1
0	0	0	0	0
0	0-	0	0	0
10	8	6	4	2

Table B	Table B.12: GPIO Header (GPIO1)					
Pin	Signal	Pin	Signal			
1	GPIO1	2	GPIO5			
3	GPIO2	4	GPIO6			
5	GPIO3	6	GPI07			
7	GPIO4	8	GPIO8			
9	VCC	10	GND			

B.13 DVI LCD panel connector (DVI1)



Table B.13:	Table B.13: DVI LCD panel connector (DVI1)					
Pin	Signal	Pin	Signal			
1	TDC0-	2	VCC			
3	TDC0+	4	TLC-			
5	GND	6	TLC+			
7	TDC1-	8	GND			
9	TDC1+	10	SC_DDC			
11	GND	12	SD_DDC			
13	TDC2-	14	HPDETT			
15	TDC2+	16	NC			
17	VCC	18	NC			
19	NC	20	NC			

B.14 LVDS Connector (LVDS1)



Table B.14: LVDS Connector (LVDS1)					
Pin	Signal	Pin	Signal		
1	LVDS_VCC	2	LVDS_VCC		
3	GND	4	GND		
5	LVDS_VCC	6	LVDS_VCC		
7	LVDS0_D0-	8	LVDS1_D0-		
9	LVDS0_D0+	10	LVDS1_D0+		
11	GND	12	GND		
13	LVDS0_D1-	14	LVDS1_D1-		
15	LVDS0_D1+	16	LVDS1_D1+		
17	GND	18	GND		
19	LVDS0_D2-	20	LVDS1_D2-		
21	LVDS0_D2+	22	LVDS1_D2+		
23	GND	24	GND		
25	LVDS0_CLK-	26	LVDS1_CLK-		
27	LVDS0_CLK+	28	LVDS1_CLK+		
29	GND	30	GND		
31	LVDS0_DDC_SC	32	LVDS0_DDC_SD		
33	GND	34	GND		
35	NC	36	NC		
37	NC	38	NC		
39	NC	40	NC		

B.15 LCD Inverter Connector (INV1)

1	2	3	4	5
	0	0	0	0

Table B.15: LCD Inverter Connector (INV1)			
Pin	Signal		
1	+12V		
2	GND		
3	BACK_ON#		
4	Brightness		
5	VCC		

B.16 SM Bus Connector (SMBUS1)



Table B.16: SM Bus Connector (SMBUS1)			
Pin	Signal		
1	VCC		
2	SMBUS CLK		
3	SMBUS Data		
4	GND		

B.17 Low Pin Count Header (LPC1)

2	4	6	8	10	12	14
0	0	0	0	0	0	0
0	0	0	0	0	0	0
1	3	5	7	9	11	13

Table B.17: Low Pin Count Header (LPC1)			
Pin	Signal	Pin	Signal
1	LPC_CLK	2	LPC_LAD1
3	LPC_RST#	4	LPC_LAD0
5	LPC_FRAME#	6	+3.3V
7	LPC_LAD3	8	GND
9	LPC_LAD2	10	NC
11	SERIRQ	12	PWROK
13	5V Standby	14	+5V

B.18 ATX power control connector (ATX1)

12	11	10	9	8	7
0	\bigcirc	0	0	\bigcirc	0
\bigcirc	\bigcirc	\bigcirc	0	\bigcirc	\bigcirc
6	5	4	3	2	1

Table B.18: ATX power control connector (ATX1)			
Pin	Signal	Pin	Signal
1	GND	7	GND
2	+5V	8	GND
3	+5V	9	5V Standby
4	GND	10	PSON#
5	+5V	11	GND
6	+5V	12	+12V

B.19 VGA Connector (VGA1)

_		-
5 \	00000	1
10	00000	6
15	\00000 <i>]</i>	11

Table B.19: VGA Connector (VGA1)				
Pin	Signal	Pin	Signal	
1	RED	9	CRT_VCCIN	
2	VGA_G	10	GND	
3	VGA_B	11	N/C	
4	N/C	12	V_SDAT	
5	GND	13	H-SYNC	
6	GND	14	V-SYNC	
7	GND	15	V_SCLK	



System Assignments

C.1 System I/O Ports

Table C.1: System I	/O Ports
Addr. range (Hex)	Device
000-01F	Interrupt controller 1, master
022-023	Chipset address
040-05F	8254 timer
060-06F	8042 (keyboard controller)
070-07F	Real-time clock, non-maskable interrupt (NMI) mask
080-09F	DMA page register
0A0-0BF	Interrupt controller 2
0C0-0DF	DMA controller
0F0	Clear math co-processor
0F1	Reset math co-processor
0F8-0FF	Math co-processor
1F0-1F8	Fixed disk
278-27F	Parallel printer port 2 (LPT3)
290-297	On-board hardware monitor
2F8-2FF	Serial port 2
360-36F	Reserved
378-37F	Parallel printer port 1 (LPT2)
3B0-3BF	Monochrome display and printer adapter (LPT1)
3C0-3CF	Graphics adapter
3D0-3DF	Color/graphics monitor adapter
3F0-3F7	Diskette controller
3F8-3FF	Serial port 1
CA0-CA7	Serial port 3
CA8-CAF	Serial port 4
CB0-CB7	Serial port 5
CB8-CBF	Serial port 6
C80-C87	Serial port 7
C88-C8F	Serial port 8
C90-C97	Serial port 9
C98-C9F	Serial port 10

C.2 DMA Channel Assignments

Table C.2: DMA Channel Assignments		
Function		
Available		
Available		
Floppy disk (8-bit transfer)		
Available		
Cascade for DMA controller 1		
Available		
Available		
Available		

C.3 Interrupt Assignments

Table C.3: Interrupt Assignments			
Priority	Interrupt#	Interrupt source	
1	NMI	Parity error detected	
2	IRQ0	Interval timer	
3	IRQ1	Keyboard	
-	IRQ2	Interrupt from controller 2 (cascade)	
4	IRQ8	Real-time clock	
5	IRQ9	Cascaded to INT 0A (IRQ 2)	
6	IRQ10	Serial communication port 3/4/5/6	
7	IRQ11	Serial communication port 7/8/9/10	
8	IRQ12	PS/2 mouse	
9	IRQ13	INT from co-processor	
10	IRQ14	Primary IDE Channel	
11	IRQ15	Secondary IDE Channel	
12	IRQ3	Serial communication port 2	
13	IRQ4	Serial communication port 1	
14	IRQ5	Available	
15	IRQ6	Available	
16	IRQ7	Parallel port 1 (print port)	

C.4 1st MB Memory Map

Table C.4: 1st MB Memory Map		
Addr. range (Hex)	Device	
E0000h - FFFFFh	BIOS	
D0000h - DFFFFh	Unused	
C0000h - CFFFFh	VGA BIOS	
A0000h - BFFFFh	Video Memory	
00000h - 9FFFFh	Base memory	





www.advantech.com

Please verify specifications before quoting. This guide is intended for reference purposes only.

All product specifications are subject to change without notice.

No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher.

All brand and product names are trademarks or registered trademarks of their respective companies.

© Advantech Co., Ltd. 2009